



20V/5A N-Channel Enhancement Mode MOSFET


Features

- Advanced trench process technology
- High Density Cell Design For Ultra Low On-Resistance
- High Power and Current handing capability

BVDSS	20	V
ID	5	A
RDS(ON)@VGS=4.5V	16	mΩ
RDS(ON)@VGS=2.5V	19	mΩ

Applications

- Low Side Load Switch
- Battery Switch
- Optimized for Power Management Applications for Portable Products, such as Aeromodelling, Power bank, Brushless motor, Main board , and Others



SOT-23

Order Information

Product	Package	Marking	Reel Size	Reel	Carton
PT2310	SOT-23	AC9T	7inch	3000PCS	180000PCS

Absolute Maximum Ratings

Symbol	Parameter	Rating	Unit	
Common Ratings (TC=25°C Unless Otherwise Noted)				
V _{(BR)DSS}	Drain-Source Breakdown Voltage	20	V	
V _{GS}	Gate-Source Voltage	±10	V	
T _J	Maximum Junction Temperature	150	°C	
T _{STG}	Storage Temperature Range	-55 to 150	°C	
I _S	Diode Continuous Forward Current	TA =25°C	5	A
Mounted on Large Heat Sink				
I _{DM}	Pulse Drain Current Tested (Silicon Limit) (Note1)	TA =25°C	13.5	A
I _D	Continuous Drain current	TA =25°C	5	A
P _D	Maximum Power Dissipation	TA =25°C	1.25	W
R _{θJA}	Thermal Resistance Junction-to-Ambient (Note2)		100	°C/W









20V/5A N-Channel Enhancement Mode MOSFET

Symbol	Parameter	Condition	Min.	Typ.	Max.	Unit
Static Electrical Characteristics @ TJ = 25°C (unless otherwise stated)						
$V_{(BR)DSS}$	Drain- Source Breakdown Voltage	$VGS=0V$ $ID=250\mu A$	20	--	--	V
I_{DSS}	Zero Gate Voltage Drain current	$VDS=20V$, $VGS=0V$	--	--	1	μA
I_{GSS}	Gate-Body Leakage Current	$VGS=\pm 10V$, $VDS=0V$	--	--	± 100	nA
$V_{GS(TH)}$	Gate Threshold Voltage	$VDS=VGS$, $ID=250\mu A$	0.4	0.65	0.8	V
$R_{DS(ON)}$	Drain-Source On-State Resistance (Note3)	$VGS=4.5V$, $ID=5A$	--	16	28	$m\Omega$
		$VGS=2.5V$, $ID=4.5A$	--	19	35	$m\Omega$
Dynamic Electrical Characteristics @ TJ = 25°C (unless otherwise stated) (Note4)						
C_{iss}	Input Capacitance	$VDS= 10V$, $VGS=0V$, $F=1MHz$	--	780	--	pF
C_{oss}	Output Capacitance		--	140	--	pF
C_{rss}	Reverse Transfer Capacitance		--	80	--	pF
Q_g	Total Gate Charge	$VDS= 10V$, $ID= 5A$,	--	11.4	--	nC
Q_{gs}	Gate-Source Charge		--	2.3	--	nC
Q_{gd}	Gate-Drain Charge		--	2.9	--	nC
Switching Characteristics (Note4)						
$t_{d(on)}$	Turn-on Delay Time	$VDD=10V$, $ID=1A$,	--	9	--	nS
t_r	Turn-on Rise Time		--	30	--	nS
$t_{d(off)}$	Turn-off Delay Time		--	35	--	nS
t_f	Turn-off Fall Time		--	10	--	nS
Source- Drain Diode Characteristics@ TJ = 25°C (unless otherwise stated)						
V_{SD}	Forward on voltage (Note3)	$IS=2A$, $VGS=0V$	--	--	1.2	V

Note:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, $t \leq 10$ sec
3. Pulse Test: pulse width ≤ 300 us, duty cycle $\leq 2\%$.
4. Guaranteed by design, not subject to production testing.

Typical Characteristics

Figure1: TJ Junction Temperature (°C)

Figure2: ID Drain Current (A)

Figure3: TJ Junction Temperature (°C)

Figure4: V_{DS} Drain-Source Voltage (V)

Figure5: V_{DS} Drain-Source Voltage (V)

Figure6: Q_g Gate Charge (nC)


20V/5A N-Channel Enhancement Mode MOSFET


Figure 7: V_{sd} Source-Drain Voltage (V)




Figure 8: I_D, Drain Current (A) vs V_{gs} Gate-Source Voltage (V)




Figure 9: V_{ds} Drain-Source Voltage (V) vs I_D-Drain Current (A)








Figure 10: Square Wave Pulse Duration (sec) vs Transient Thermal Impedance

20V/5A N-Channel Enhancement Mode MOSFET
Test Circuit and Waveform:

Figure A Gate Charge Test Circuit & Waveforms

Figure B Switching Test Circuit & Waveforms

Figure C Unclamped Inductive Switching Circuit & Waveforms

SOT-23 Package Outline Dimensions (Units: mm)



COMMON DIMENSIONS (UNITS OF MEASURE IS mm)			
	MIN	NORMAL	MAX
A	2.800	2.900	3.000
B	1.200	1.300	1.400
C	0.900	1.000	1.100
C1	0.500	0.550	0.600
D	2.250	2.400	2.550
L	0.300	0.400	0.500
h	0.010	0.050	0.100
b	0.300	0.400	0.500
e	1.90 TYPE		
e1	0.95 TYPE		
θ_1	7° TYPE		
θ_2	7° TYPE		
θ	0° ~ 7°		